## Operational Semantics

- Useful for exploraration
- Useful to guide **implementation**
- Useful to show correctness of implementation

- Derived assertions correspond to **individual test cases**
- More general statements need to be shown at the meta-level
- **Not useful** to **prove general properties** of programs
  - **termination**
  - **correctness**



## Correctness

- ***Correctness is always relative to a specification***
- A specification is — in general — a logical formula
  — many different logics are used!
- A program is **correct** iff it **satisfies** its specification
- Using logical methods to prove correctness is called **formal verification**
  - Using (normally human-aided) ***syntactic*** methods: **proving**
    — normally necessary for functional requirements
  - Using (exhaustive, automated) ***semantic*** methods: **model checking**
    — most useful for safety & lifeness properties (finite models)
- ***How do you show a specification is correct?***
  - **Validation:** Are we building the right product?
  - **Verification:** Are we building the product right?



## Axiomatic Semantics

Derivation of judgements written as "Hoare triples"

$$\{P\}S\{Q\}$$

where $P$ and $Q$ are formulae denoting conditions on **execution states**:

- $P$ is the **precondition**
- $S$ is a program fragment (statement)
- $Q$ is the **postcondition**

A Hoare triple $\{P\}S\{Q\}$ has two readings:

**Total correctness:** ***If*** $S$ starts in a state satisfying $P$,
***then it terminates*** and its terminating state satisfies $Q$
— "$S$ **is totally correct with respect to** $P$ and $Q$"

**Partial correctness:** ***If*** $S$ starts in a state satisfying $P$ and ***terminates***,
***then*** its terminating state satisfies $Q$
— "$S$ **is partially correct with respect to** $P$ and $Q$"

("terminates" means "terminates without run-time error")



## Axiomatic Semantics vs. Operational Semantics

- Operational semantics relates **states** via statements
- Axiomatic semantics relates **conditions on states** via statements

***Therefore:***

- Operational semantics facilitates investigation of examples ("***testing"***)
- Axiomatic semantics facilitates relating a program with its specification
  — **verification**

## Relating Axiomatic and Operational Semantics

- Operational semantics relates **states** via statements
- Axiomatic semantics relates **conditions on states** via statements

Relating states with conditions on states:

- " $s \models P$ " means "condition $P$ **holds**, or **is valid**, in state $s$"

For example:
- $\{x \mapsto 5, y \mapsto 7\} \models x > 0$
- $\{x \mapsto 5, y \mapsto 7\} \models \sum_{i=0}^{10} = 55$
- $\{x \mapsto 5, y \mapsto 7\} \not\models x > y$



## Relating Axiomatic and Operational Semantics

- Operational semantics relates **states** via statements
- Axiomatic semantics relates **conditions on states** via statements

Relating states with conditions on states:
- " $s \models P$ " means "condition $P$ **holds**, or **is valid**, in state $s$"

The two readings of a Hoare triple $\{P\}S\{Q\}$:

**Partial correctness:** ***If*** $S$ starts in a state satisfying $P$ and ***terminates***,
***then*** its terminating state satisfies $Q$
***I.e.: For all*** states $\sigma_1$ and $\sigma_2$,
***if*** $\sigma_1 \models P$ ***and*** $\sigma_1(S) \Rightarrow \sigma_2$, ***then*** $\sigma_2 \models Q$

**Total correctness:** ***If*** $S$ starts in a state satisfying $P$,
***then it terminates*** and its terminating state satisfies $Q$
***I.e.: For all*** states $\sigma_1$, ***if*** $\sigma_1 \models P$,
***then there is*** a state $\sigma_2$
***such that*** $\sigma_1(S) \Rightarrow \sigma_2$, ***and*** $\sigma_2 \models Q$



## Proving Partial and Total Correctness

**Total correctness** of $\{P\}\ S\ \{Q\}$

***is equivalent to***

**partial correctness** of $\{P\}\ S\ \{Q\}$ ***together with*** the fact that $S$ terminates when started in a state satisfying $P$

$\Rightarrow$ usually, separate **termination proof!**

- For partial correctness, it is relatively easy to give a **direct proof calculus**
- Proving partial correctness therefore does not need operational semantics
- In the following, we will study and use this calculus
- (Termination proofs use different methods — ***well-ordered*** sets)

Unless explicitly mentioned, we read " $\{P\}\ S\ \{Q\}$ " as meaning **partial correctness**.



## Derivation Rules for Sequencing, Conditionals, Loops

**Logical consequence:**
$$\frac{P \Rightarrow P' \qquad \{P'\}S\{Q'\} \qquad Q' \Rightarrow Q}{\{P\}S\{Q\}}$$

**Sequence:**
$$\frac{\{P\}S_1\{R\} \qquad \{R\}S_2\{Q\}}{\{P\}S_1;\ S_2\{Q\}}$$

**Conditional:**
$$\frac{\{P \wedge b\}S_1\{Q\} \qquad \{P \wedge \neg b\}S_2\{Q\}}{\{P\}\textbf{if } b \textbf{ then } S_1 \textbf{ else } S_2 \textbf{ fi}\{Q\}}$$

**while-Loop:**
$$\frac{\{INV \wedge b\}S\{INV\}}{\{INV\}\textbf{while } b \textbf{ do } S \textbf{ od}\{INV \wedge \neg b\}}$$

# Axiom Schema for Assignments

$$\{P[x \setminus e]\}x := e\{P\}$$

**Examples:**

- $\{2 = 2\}x := 2\{x = 2\}$
- $\{x + 1 = 2\}x := x + 1\{x = 2\}$
- $\{n + 1 = 2\}x := n + 1\{x = 2\}$

***Typically,*** Hoare triples are derived starting from the ***postcondition***

— **backward reasoning**.

Considering this axiom schema as a way to ***calculate*** a precondition from assignment and postcondition, it calculates the **weakest precondition** that completes a valid Hoare triple.



# Example Verification

$$\{\mathsf{True}\}k := 0;\ s := 0;\ \textbf{while}\ k \neq n\ \textbf{do}\ k := k + 1;\ s := s + k\ \textbf{od}\{s = \sum_{i=1}^{n} i\}$$

$$\Leftarrow \{\mathsf{True}\}k := 0;\ s := 0;\ \textbf{while}\ k \neq n\ \textbf{do}\ k := k + 1;\ s := s + k\ \textbf{od}\{s = \sum_{i=1}^{k} i \wedge k = n\}$$

$$\Leftarrow \{\mathsf{True}\}k := 0;\ s := 0\{s = \sum_{i=1}^{k} i\}$$
$$\wedge\ \{s = \sum_{i=1}^{k} i\}\textbf{while}\ k \neq n\ \textbf{do}\ k := k + 1;\ s := s + k\ \textbf{od}\{s = \sum_{i=1}^{k} i \wedge k = n\}$$

$$\Leftarrow \{\mathsf{True}\}k := 0\{0 = \sum_{i=1}^{k} i\}$$
$$\wedge\ \{0 = \sum_{i=1}^{k} i\}s := 0\{s = \sum_{i=1}^{k} i\}$$
$$\wedge\ \{s = \sum_{i=1}^{k} i \wedge k \neq n\}k := k + 1;\ s := s + k\{s = \sum_{i=1}^{k} i\}$$



# Example Verification (ctd.)

$$\Leftarrow (\mathsf{True} \Rightarrow 0 = \sum_{i=1}^{0} i\ )\ \wedge\ \{0 = \sum_{i=1}^{0} i\}k := 0\{0 = \sum_{i=1}^{k} i\}$$
$$\wedge\ \mathsf{True}$$
$$\wedge\ \{s = \sum_{i=1}^{k} i \wedge k \neq n\}k := k + 1\{s + k = \sum_{i=1}^{k} i\}$$
$$\wedge\ \{s + k = \sum_{i=1}^{k} i\}s := s + k\{s = \sum_{i=1}^{k} i\}$$

$$\Leftarrow \mathsf{True}$$
$$\wedge\ s = \sum_{i=1}^{k} i \wedge k \neq n \Rightarrow s + k + 1 = \sum_{i=1}^{k+1} i$$
$$\wedge\ \{s + k + 1 = \sum_{i=1}^{k+1} i\}k := k + 1\{s + k = \sum_{i=1}^{k} i\}$$
$$\wedge\ \mathsf{True}$$

$$\Leftarrow \mathsf{True}$$



# Finding Proofs of Partial Correctness

- Normally, **Backward reasoning** drives the proof:

  Start to consider the postcondition and how the last statement achieves it
- **Forward reasoning** from the precondition can be useful for simple assignment sequences and for exploration
- For **while** loops, the postcondition needs to consist of
  - the **invariant** of this loop, and
  - the negation of the **loop** condition

  ***Auxiliary variables used in a loop are usually involved in the invariant!***

  Given a loop "**while** $b$ **do** $S$ **od**" and a postcondition $Q$, use the consequence rule to strengthen $Q$ to $Q'$, such that
  - $Q' \Rightarrow Q$ (strengthening)
  - $Q'$ involves all auxiliary variables — **generalisation!**
  - $Q'$ is of shape $INV \wedge \neg b$

## Simultaneous Assignments

$$\{P[x_1 \setminus e_1, \ldots, x_n \setminus e_n]\}(x_1, \ldots, x_n) := (e_1, \ldots e_n)\{P\}$$

**Examples:**

- $\{1 = 2^0\}(k, n) := (0, 1)\{n = 2^k\}$
- $\{y \geq x + 2\}(x, y) := (y, x)\{x \geq y + 2\}$

Simultaneous assignments

– shorten code

– save auxiliary variables (for example for swapping)

– make proofs easier

– **require simultaneous substitution**



## Example Problems (with Simultaneous Assignments)

$\{n \geq 0\}$ $(y, a, b) := (0, 1, 1)$ **;**
**while** $y \neq n$ **do** $(y, a, b) := (y + 1, b, a + b)$ **od** $\{a = fib_n\}$

---

Given an $n$-element C-like array $s$, prove partial correctness:

$\{\mathsf{True}\}$
$(i, a) := (0, 0)$ **;**
**while** $i \neq n$
**do** **if** $x = s[i]$
**then** $(i, a) := (i + 1, a + 1)$
**fi od**
$\{a = \#\{j : \mathbb{N} \mid s[j] = x \wedge 0 \leq j < n\}\}$

What does this program do?



## Fibonacci

$\{n \geq 0\}$ $(y, a, b) := (0, 1, 1)$ **;**
**while** $y \neq n$ **do** $(y, a, b) := (y + 1, b, a + b)$ **od** $\{a = fib_n\}$

$\Leftarrow$ ⟨ ( right consequence ) ⟩
$\{n \geq 0\}\ P\ \{a = fib_y \wedge b = fib_{y+1} \wedge y = n\}$
$\wedge\ (a = fib_y \wedge b = fib_{y+1} \wedge y = n \Rightarrow a = fib_n)$

$\Leftarrow$ ⟨ ( sequence , logic ) ⟩
$\{n \geq 0\}\ (y, a, b) := (0, 1, 1)\ \{a = fib_y \wedge b = fib_{y+1}\} \wedge$
$\{a = fib_y \wedge b = fib_{y+1}\}$**while** $y \neq n$ **do** $A$ **od**$\{a = fib_y \wedge b = fib_{y+1} \wedge y = n\}$
$\wedge$ True



## Fibonacci (ctd.)

$\Leftarrow$ ⟨ ( left consequence , **while** ) ⟩
$(n \geq 0 \Rightarrow 1 = fib_0 \wedge 1 = fib_{0+1})$
$\wedge\ \{1 = fib_0 \wedge 1 = fib_{0+1}\}\ (y, a, b) := (0, 1, 1)\ \{a = fib_y \wedge b = fib_{y+1}\}$
$\wedge\ \{a = fib_y \wedge b = fib_{y+1} \wedge y \neq n\}\ (y, a, b) := (y + 1, b, a + b)$
$\{a = fib_y \wedge b = fib_{y+1}\}$

$\Leftarrow$ ⟨ ( arithmetic , assignment , left consequence ) ⟩
True $\wedge$ True
$\wedge\ (a = fib_y \wedge b = fib_{y+1} \wedge y \neq n \Rightarrow b = fib_{y+1} \wedge a + b = fib_{(y+1)+1})$
$\wedge\ \{b = fib_{y+1} \wedge a + b = fib_{(y+1)+1}\}\ (y, a, b) := (y + 1, b, a + b)$
$\{a = fib_y \wedge b = fib_{y+1}\}$

$\Leftarrow$ ⟨ ( arithmetic , assignment ) ⟩
True $\wedge$ True